

Technical Datasheet - Listello

Aluminium Listello - LPA


Product Description

Genesis LPA is a decorative Aluminium profile designed to create a feature in ceramic wall tile installations. The profile face is slightly curved to emphasis the texture transition from ceramic to Aluminium. The suitability of aluminium must be determined if Chemical or mechanical stresses are anticipated.


Dimensions and Colour

All available in 2.5m lengths and 10mm and 25mm widths in Matt or Polished Silver finishes - see the Metals colour chart for depth/finish combinations.

Range



LPA100



LPA250

Technical Details

Profiles are available in different anodised finishes and powder coated finishes - All natural Aluminium (Mill Finish) has an oxide film of approx 0.2 microns, when Mechanically & Chemically polished the anodising process increases this to 5 microns, up-to 20 for the Matt finish and 100 for Powder coated.



Maintenance

Genesis LPA profiles do not require any special maintenance. Oxidation films on Aluminium may be removed with a common polishing agent; however, they do reoccur. Damaged anodised finishes may only be repaired by recoating.

Aluminium must be tested to verify its suitability if chemical stresses are anticipated. Cementitious materials, in conjunction with moisture, become alkaline. Since aluminium is sensitive to alkaline substances, exposure to the alkali (depending on the concentration and time of exposure) may result in corrosion (aluminium hydroxide formation). Therefore, it is important to remove adhesive or grout residue from visible surfaces. In addition, ensure that the profile is solidly embedded in the setting material and that all cavities are filled to prevent the collection of alkaline water.

The anodised layer creates a finish that retains a uniform appearance during normal use. The surface, however, is susceptible to scratching and wear and may be damaged by tile adhesive, mortar, or grouting material. Therefore, setting materials must be removed immediately. Otherwise, the description regarding aluminium applies.

Installation

1. Select LPA width according to the desired effect either 10mm or 25mm.
2. Trowel tile adhesive over the area.
3. Press the LPA profile into place and align on top of the already laid tile.
4. Solidly embed the tiles so that the tiled surface is flush with the top of the profile, the profile should not be higher than the tiled surface.
5. Fill the joint completely with grout.

Aluminium AA 6063 T6 / UNS A96063 anodised to DIN 17611

Si%	0.2-0.6
Fe%	0.35
Cu%	0.1
Mn%	0.1
Mg%	0.45-0.9
Zn%	0.1
Ti%	0.1
Cr%	0.1
Al	Balance

P.V.C. Trim • Stair Nosings • Movement Joints • Transitions • Entrance Matting • Edge Protection • Metal Profiles • Tactiles • Tools

LITOKOL®
HI-PERFORMANCE BUILDING PRODUCTS

Litokol spa - via G. Falcone, 13/1 - Rubiera (RE) - Italy
Tel.+39.0522.622811- info@litokol.it - www.litokol.it

 **Genesis**
For the Perfect Finish

