



DILUENT D1

DILUENT FOR PRIMER P1

DESCRIPTION

Special organic solvent based diluent.

PACKAGING

10-litre cans - 760 litre standard pallets

FIELDS OF APPLICATION

Suitable for diluting the single component polyurethane primer, Primer P1, as a penetration promoter on absorbent cementitious substrates. It is recommended to use Primer P1 with other products.

APPLICATION

Diluent D1 should be mixed with Primer P1 as follows
1 : 1 or 1 : 2 depending on the substrate's degree of absorption.

WARNINGS

Only use the product to dilute Primer P1

IDENTIFICATION DATA

Appearance	liquid
Colour	Colourless
Smell	Typical of solvents
Custom classification	3814 0090
Preservation time	6 months in its original packaging. Store at a temperature between +5°C and +25°C

APPLICATION DATA

Dilution	1 : 1 - 2 : 1 with Primer P1
Application	To be used solely as a diluent for Primer P1

INFORMATION ON SAFETY

Refer to the product's safety sheets available upon request

PRODUCT FOR PROFESSIONAL USE

Although the information in this technical chart is from our best experience, it is merely indicative.
Each specific case must be subjected to practical preliminary tests by the user who undertakes the responsibility for the final work result.

Sheet No. 704

Revision No. 1

Date: May 2007

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy
Tel. +39 0522 622811 Fax +39 0522 620150
www.litokol.it email: info@litokol.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =