

Declaration of Performance: N° **CPR-IT204**

1. Unique identification code of the product-type: **LITOACRIL PLUS**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**IMPROVED DISPERSION ADHESIVE FOR CERAMIC TILES (D2)**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**IMPROVED DISPERSION ADHESIVE FOR TILING INTERNAL FLOORS AND WALLS**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**LITOKOL S.p.A. – Via G. Falcone 13/1 – Rubiera (RE) – Italy – [www.litokol.it](http://www.litokol.it)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by harmonised standard:  
**The notified testing laboratory AIDICO Instituto tecnologico de la construccion - Valencia - Spain - N°1170, performed the determination of the shear adhesion strength on sample taken by manufacturer, under system 3, and issued the test report N°AE062052**

8. In the case the declaration of performance concerning a construction product for which a European Technical Approval has been issued:

**Not applicable**

9. Declared performance


| Essential characteristics                        | Performance               | Harmonised technical specification |
|--|---------------------------|------------------------------------|
| Reaction to fire                                 | Class E                   | EN 12004:2007                      |
| Initial shear adhesion strength                  | $\geq 1 \text{ N/mm}^2$   |                                    |
| Shear adhesion strength after heat ageing        | $\geq 1 \text{ N/mm}^2$   |                                    |
| Shear adhesion strength at elevated temperatures | $\geq 1 \text{ N/mm}^2$   |                                    |
| Shear adhesion strength after water immersion    | $\geq 0,5 \text{ N/mm}^2$ |                                    |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by **Alessandro Turini – Managing Director**

**Rubiera, 01/07/2013**

(place and date of issue)

  
.....  
(signature)