



## LITOCOLOR

### COLOURED TREATMENT FOR CEMENTITIOUS JOINTS

#### DESCRIPTION

LITOCOLOR is a polyurethane paint ready to use, coloured, for the waterproofing treatment idro-oleo repellent of cement escapes.

#### PACKAGING

Pots 1 litre

#### FIELD OF APPLICATION

Indicated for the superficial treatment of cement escapes that show a colouring not uniform, in order to bestow on the same escapes a homogeneous colour.

Appropriate for applications both inside and external in floor and wall.

#### PRELIMINARY VERIFICATION AND PREPARATION OF ESCAPES

Make sure first of all the escapes to treat be clean, dry, compact and that there isn't presence of humidity. Before the treatment is necessary that be the use mortar for the pose of the ceramics, that the cement stuccoing had complete the cycle of maturation. Prospective efflorescence or residuals of stuccoing went remove through a sour wash in base of LITOCLEAN or LITOCLEAN PLUS ( read relative specifications ). Than the wash, when the escapes will result completely dry, you will can go ahead with the treatment in base of LITOCOLOR.

#### APPLICATION

Coalesce accurately the product contained in the pot with a wire slice at the beginning of the work and during the application, for guarantee a perfect homogeneity of the colour. Not apply the product with temperature lower than +10 C or higher than +25 C.

In the case of applications in external with warm climate, advise to utilize the product just in the first hours of the morning.

In this way will avoid unpleasant inconvenient due to too rapid drying up of the product, that for this reason remained all on the surface without penetrate in depth and without guarantee an able adherence and stability in the time.

Apply a first hand with flat brush (choose the dimension in operation of the generosity of the escapes) and finish the first hand, apply directly the second hand wet over wet.

The number of the hand necessary for obtain a good cover, depends from the permeability and from the colour of the escapes, and from the colour of the treatment selected.

On the average consider sufficient the two hand.

The product leaks on the border of the lies must be immediately remove with a duster cloth before the drying up. The operation may be easier if the duster cloth comes lightly humid with methylated spirits.

The application in excess of the product in the escapes, could be produce a sudden degradation of the treatment, we advise therefore, in case apply too material, to remove immediately with cloth of dry cotton.

The escapes treat with LITOCOLOR will can be walkable then 24 hours.

Explain whatever that the complete maturation will have then about 5-7 days.

We advise so to avoid for the first time to drag tools or weigh furniture over the surface.

For the cleaning of the floor will can utilize detergent suitable at the same floor, with warning of not utilize products that contain solvent.

#### WARNING

Don't apply the product in case of lies or natural stone with absorb surfaces type poached Tuscan. In this case the product comes preoccupied also from the lies give back impossible the removal.

In cases doubt make a preliminary proof.

Apply the product with temperatures included between +10°C and +25°C.

Don't use the product for applications not relate on the present specifications.

For the cleaning of the tools utilize methylated spirits or nitro paint thinner.

Don't append water or solvents to the product.

The final shade of the product apply can differ lightly from the paint of case in function of permeability of the support.

#### IDENTIFICATION DATA

Aspect	Fluid
Smell	Distinctive
Colour	Are available all colouring of the range of the cement sealing Litochrom 0-2, 1-6, 3-15 and any paint RAL and NCS on request
Flammability	Yes
Customs classification	3208 9091
Time of preservation	12 month in the original packaging

#### APPLICATIONS DATA

Application	Flat brush
Temperature of permission application	From +10°C to +25°C
Time of drying up	6-8 hours
Walk on time	24 hours
Ready for use	5- 7 days
Consumption	Roughly 1 litre for 50/60 m² of ceramic shape with formed 25x25 cm

#### SAFETY INFORMATION

Consult the Material Safety Data Sheet, available on request.  
PRODUCT FOR PROFESSIONAL USE.

Although the information in this technical sheet is source of our best experience, it is merely indicative.

Each specific case must be subjected to practical preliminary tests by the user who undertakes the responsibility for the final work result.

Sheet n.532

Revision n.2

Date: March 2012

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy

Tel. +39 0522 622811 Fax +39 0522 620150

www.litokol.it email: info@litokol.it